

1. A display case, comprising:

a first section including a top wall, a bottom wall and a back wall connected between said top and bottom walls, said bottom wall being formed with a bracket having a first arm and a second arm
5 connected to said first arm, a space being formed between said bottom wall and said second arm which is adapted to receive a shelf;

a second section including a first side wall, a second side wall and a front wall connected between said first and second side walls, said second section being joined with said first section so that
10 said first and second side walls of said second section abut said back wall of said first section and said top and bottom walls of said first section contact said front wall and said first and second side walls of said second section to form a closed interior;

a mounting device insertable through said second arm of
15 said first section, said mounting device being adapted to contact a shelf received within said space between said bottom wall and said second arm to secure said first and second sections to the shelf.

2. The display case of claim 1 in which said top wall, said bottom wall and said back wall of said first section are permanently interconnected to form a one-piece structure.

3. The display case of claim 1 in which said first side wall, said second side wall and said front wall of said second section are permanently interconnected to form a one-piece structure.

4. The display case of claim 1 in which said second arm of said bracket is substantially parallel to said bottom wall.

5. The display case of claim 1 in which said top wall of said first section is formed with an upper lip extending toward said bottom wall thereof and said bottom wall of said first section is formed with a lower lip extending toward and in alignment with said upper lip, said front wall of said second section contacting said upper lip of said top wall and said lower lip of said bottom wall to maintain said first and second sections in engagement with one another.

6. The display case of claim 1 in which each of said side walls of said second section is formed with a flange which abuts said back wall of said first section when said first and second sections are joined together, at least one fastener being inserted through said back wall into each of said flanges to secure said first and second sections together.

7. The display case of claim 1 in which said mounting device is a thumb screw which extends through said second arm of said bracket and is adapted to engage the bottom of a shelf.

8. The display case of claim 1 in which a mirror is mounted to said back wall of said first section.

9. The display case of claim 1 in which at least said first and second side wall, said top wall and said front wall are formed of a transparent material to permit viewing of said closed interior.

10. A display case, comprising:

a one-piece first section including a top wall, a bottom wall and a back wall permanently connected between said top and bottom walls, said top wall being formed with an upper lip extending
5 toward said bottom wall, said bottom wall being formed with a bracket having a lower lip extending toward said upper lip and in alignment therewith, a first arm extending in a direction away from said lower lip and a second arm connected to said first arm, a space being formed between said bottom wall and said second arm which is
10 adapted to receive a shelf;

a one-piece second section including a first side wall, a second side wall and a front wall permanently connected between said first and second side walls, each of said first and second side walls being formed with a flange, said second section being slid into
15 engagement with said first section so that said front wall contacts said upper and lower lips, said flange of each of said side walls abuts said back wall and said top and bottom walls contact said front wall and said first and second side walls to form a closed interior;

a mounting device insertable through said second arm of
20 said first section, said mounting device being adapted to contact a shelf received within said space between said bottom wall and said second arm to secure said first and second sections to the shelf;

at least one fastener extending through said back wall of
said first section into said flange of each of said first and second side
25 walls of said second section to secure said first and second sections
together.

11. The display case of claim 10 in which said second arm of
said bracket is substantially parallel to said bottom wall.

12. The display case of claim 10 in which said mounting
device is a thumb screw which extends through said second arm of
said bracket and is adapted to engage the bottom of a shelf.

13. The display case of claim 10 in which a mirror is
mounted to said back wall of said first section.

14. The display case of claim 10 in which at least said first
and second side wall, said top wall and said front wall are formed of a
transparent material to permit viewing of said closed interior.